State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-21-302-1 Relating to Certification of New Heavy-Duty Engines and Vehicles

CUMMINS ENGINE COMPANY, INC.

Pursuant to the authority vested in the Air Resources Board at Sections 43100, 43101, and 43102 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned at Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9; and

Pursuant to the December 15, 1998 Settlement Agreement between the Air Resources Board and Cummins Engine Company, Inc. and any modifications to the Settlement Agreement;

IT IS ORDERED AND RESOLVED: That the following engines and emission control systems produced by the manufacturer are certified for use in motor vehicles with a manufacturer's gross vehicle weight rating (GVWR) over 14,000 pounds:

Model Year: 2001

Fuel Type: Diesel

	Disp	lacement	Exhaust Emission Control
Engine Family	<u>Liters</u>	Cubic Inches	Systems and Special Features
1CEXH0505CAO	8.3	505	Turbocharger
			Charge Air Cooler
			Powertrain Control Module
			Direct Diesel Injection

Engine models and codes are listed on the attachments.

BE IT ORDERED AND RESOLVED: That the following are the certification exhaust emission standards (Title 13, California Code of Regulations, Section 1956.8) and certification emission levels for this engine family in grams per brake horsepower-hour (g/bhp-hr) under the Federal Test Procedure ("FTP"):

	Total	Carbon	Nitrogen	Particulate
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Matter</u>
Standards	1.3	15.5	4.0	0.10
Certification	0.1	0.9	3.9	0.08

BE IT FURTHER RESOLVED: That pursuant to the Settlement Agreement and any modifications thereof, the aforementioned engine family is also subject to emission standards under the EURO III tests in the Settlement Agreement, including a "Not-to-Exceed" nitrogen oxides emission standard of 5.0 g/bhp-hr. The following are the emission standards and certification levels, in g/bhp-hr, under the EURO III tests:

	Total <u>Hydrocarbons</u>	Carbon <u>Monoxide</u>	Nitrogen Oxides	Particulate Matter
Standards	1.3	15.5	4.0	0.10
Certification	0.1	0.4	3.7	0.07

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Sections 2035 *et seq.*).

BE IT FURTHER RESOLVED: That the aforementioned engine family has been conditionally certified subject to the following conditions:

- 1. The Settlement Agreement is in effect.
- 2. The manufacturer is in compliance with all applicable certification requirements of the Settlement Agreement.

Engines certified under this Executive Order must conform to all applicable California emission regulations and to all applicable terms and conditions of the Settlement Agreement.

The Bureau of Automotive Repair will be notified by copy of this order and attachments.

Executive Order A-21-302, dated December 22, 2000, is hereby superseded by Executive Order A-21-302-1.

Executed at El Monte, California this

124

_ day of March 2001.

R. B. Summerfield, Chief

Mobile Source Operations Division

Engine Model Framary Form

Manufacturer: Cummins Engine Company, Inc.

On-highway HDDE

Engine category:

EPA Engine Famiy: 1CEXH0505CAO

į

Mfr Family Name: 4130

Process Code: New Submission

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torqu	8.Fuel Rate: 9.Emission Control (lbs/hr)@peak torque Device Per SAE J1930
2694,FR90673	ISC 315	315@2000	163	110	950@1300	179	ፈላ 5.87	78.5 PDI PCM, TC, CAC →
2694;FR90818	ISC 315	315@2000	157	106	950@1300	179	78.5	PCM, 88 CAC 12
2693,FR90671	ISC 300	300@2000	128	106	860@1300	166	72.6	PCM, TC, CAC
2693,FR90672	ISC 300	300@2000	158	106	840@1300	162	70.9	PCM, TC, CAC
2692,FR90670	ISC 285	285@2000	147	599.3	800@1300	154	67.5	PCM, TC. CAC
2691,FR90669	ISC 260	260@2000	138	93.1	800@1300	149	65.3	▼ PCM, TC, CAC

ATTACHMENT

A-21-302-1